



- Hatch cover: Grade A / Aluminium / Stainless Steel ; 8 mm
- Coaming: 75x50x7 Steel / Aluminium / Stainless Steel
- Cleats: Cast stainless steel: 1.4408 / ATSM CF8M equivalent to 1.4404 / AISI 316
- Mechanism: Stainless Steel 1.4404 / AISI 316L
- Seal: Seal 42.5x20.4 EPDM 30 shore
- Wedge: Brass
- Hinge: Stainless Steel or Aluminium with Orkot® bearing and Stainless Steel Axle
  
- Insulation : Rockwool Marineslab 55 or FireMaster Marine Plus Blanket :40mm / 70 kg m<sup>3</sup>
- Clear Opening: HS x W (min. 650x650 / max. 850x850)
- Cut in plate: HS + 75 x W + 75 R = 137.5
- Outside dimensions: HS + 150 x W + 150
- Handle length: L = 300/360 mm
- Pressure: 0-5 mWc
- Gasspring: Steel standard
  
- Stainless Steel ***Optional***
- ESI openholder ***Optional***
  
- Locking pin: Inside ***Optional***
- Polishing: Handle ***Optional***
  
- Cleat system ***Optional***
- Hinge pin & rose ***Optional***

	RM	29-6-2021	-
Revision Description	Name	Date	Rev
	Status:	WorkInProgress	
	Engineer:	RM	7-12-2018
American projection:	Description: WT Musketeer Hatch  Angle bar frame   St gassprings		
 <small>info@winel.nl www.winel.nl +31 (0)592 366 060</small>	Reference: Winel product catalog		
	Drawing number: <b>9541.41 XXX</b>		Rev. Sheet Size
			- 1 / 1 A2
The drawing and design shown is our property and may not be used or disclosed for any third person without our specific written approval.			